

Asona Diffusion™

Flat Sound Reflecting Ceiling Panel

Technical Data sheet



ASONA

Description.

Asona Diffusion™ is a robust sound reflecting ceiling panel designed to compliment the Triton™ range of sound absorbing ceiling panels. With the same crisp Sonatex™ finish Diffusion™ can be mixed and matched with Triton™ absorber panels to enhance speech clarity, intelligibility and the tonal qualities of played music.

Application.

Diffusion™ is ideal for use in music rooms as well as traditional didactic style teaching spaces, lecture theatres and some classroom settings where it is desirable for the teachers voice to be projected to the back of the room.

Composition.

Manufactured from fire resistant Sonatex™ 250 kg/m³ composite facer panel laminated to an 750 kg/m³ 10 mm thick plasterboard backer panel. Made in NZ.

Benefits.

- Good sound reflection for music tone and speech clarity.
- Crisp clean white finish
- High light reflectance
- Helps attenuate and muffle rain noise under metal roofing



- Durable high density composite construction resists damage from knocks and scraps.
- Can support light fixtures up to 2 kg.
- Made in NZ, short lead times versus imports
- PE backed option helps prevent condensation damage under cold roof linings.
- Low environmental impact, product and packaging can be recycled/ reused.

Technical Specifications

Item #	Size (nominal)	Edge
GC31233A	12 x 600 x 600 mm	A / Square
GC31234A	12 x 600 x 1200 mm	A / Square

Sound Absorption Rating: Diffusion α_w 0.15; NRC 0.10 per ASTM C423, ISO 354 E-200 Test report T0516-2

Panel	Hz	125	250	500	1000	2000	4000
Diffusion	α_p	0.20	0.10	0.05	0.05	0.15	0.20

Accessibility:

All panels are demountable and accessible.

Back loading:

Max. 3.5 kg/m², point loads over 2 kg shall be independently supported.

Colour:

White, other to order

Environmental impact:

Product and packaging can be reused/recycled.

Fire Reaction:

AS1530 pt 3.

Smoke developed 3, spread of flame 0.

Humidity:

Max 95% R/H at 30°C.

Light reflectance:

ASTM C1477 LR-1, >75%

Maintenance:

Clean with vacuum, soft brush or damp cloth. Re-surfacing available, consult Asona.

NZ Building Code:

Clause B2—durability, 5 years

Service Panels:

Available with protective plastic film covering to help keep panels cleaning during the construction phase.

Thermal Resistance:

R 0.1 m²°C/W

Weight:

7.5 kg/m²

Patent Pending:

NZP531386

Installation:

Shall not commence until the building is water tight and dry. Light fittings shall be independently supported if over 2 kg, use hold down clips in seismic areas. Store panels flat on pallets in a clean dry place.

Specification:

Ceiling shall be Asona Diffusion™ composite ceiling system manufactured by Asona Ltd, tel: 09 525 6575, fax: 09 525 6579 item # GC31234A, 1200 x 600 x 12mm mm, colour white, installed on proprietary colour/texture matched TFX glass tissue faced two way exposed suspension system with 2 x hold down clips per panel. Service panels shall be supplied with protective strippable plastic film facing #PF.

Asona Ltd

P.O Box 96-241 Balmoral,
Auckland, New Zealand

Sales:

Tel: + 64 (0)21 50 57 40

Email: info@asona.co.nz

Web: www.asona.co.nz

Factory:

5B Monier Place

Mt Wellington

Auckland, New Zealand

Tel: 09 525 6575

Fax: 09 525 6579

© Copyright ASONA Ltd 2007

Asona, Diffusion, Sonatex, Triton are trade marks of Asona Ltd
All dimensions are nominal, We reserve the right to change specifications
Ref. Diffusion-0703