

# triton 25w<sup>TM</sup>

HIGH SOUND ABSORBING CEILING PANEL



TECHNICAL DATA SHEET - BPIR CLASS 1



# triton 25w™

**Acoustic Ceiling Panel, Perforated LPL Finish  
NRC to 0.90**

## Technical Data Sheet - BPIR Class 1

Triton 25 Woodlook™ is a cost effective fire group 1-S perforated acoustic ceiling panel with a wood look low pressure laminate (LPL) finish. Made in NZ, the high sound absorbing panels are designed to control unwanted noise reverberation. Panels are available in a range of sizes and decorative wood print (or colour) Sonaris™ perforated acoustic laminate patterns.

### Application

Triton 25 Woodlook™ is ideal for use in corporate offices, lobbies, showrooms, retail, hospitality, libraries and schools.

### Composition

Made in NZ from 48 kg/m³ bio-soluble glass wool absorber with a perforated low pressure laminate finish and tissue backed.

### Features & Benefits

- Attractive perforated wood panel look at lower cost compared to traditional perforated wood panels.
- Fire Group 1-S rating without cost of intumescent coatings.
- High sound absorption rating to control reverberation, up to NRC 0.90 depending on selected perforation pattern.
- Light weight for superior safety in seismic prone areas.
- Economical grid and tile ceiling system, 60% lower installed cost vs traditional perforated FR plywood or FR MDF ceilings.
- Broad range of perforated patterns to select from as well as custom patterns to order for design flexibility.
- Low VOC, low carbon solution with 90% by volume NZ made/ sourced material content including over 80% recycled post consumer waste.



- Made in NZ for short lead times. Product stewardship Renew and Reuse program available. Packaging take back and reuse scheme available (NZ only).
- Durable and dimensionally stable, suitable for high humidity and non air conditioned spaces.


### Sound Absorption Rating:

NRC 0.55- 0.90 per ASTM C423 ISO 354 E-200, Test reports T2216-01>09

Item	Open Area	NRC	125 Hz	250 Hz	500 Hz	1K Hz	2K Hz	4K Hz
Non perf	0%	0.35	0.60	0.35	0.55	0.35	0.20	0.15
RS12-150	3%	0.55	0.65	0.60	0.70	0.50	0.30	0.25
P15-60	4.9%	0.70	0.65	0.75	0.80	0.65	0.50	0.35
S7-75	9.5%	0.75	0.65	0.80	0.85	0.70	0.60	0.40
P12-30-40	9.5%	0.80	0.65	0.85	0.85	0.75	0.65	0.45
S4-25	14.6%	0.85	0.60	0.90	0.95	0.85	0.85	0.70
P50-100	19.6%	0.85	0.60	0.90	0.90	0.85	0.75	0.60
P19-19	33%	0.90	0.55	0.85	0.95	0.90	0.95	0.90


(Special sizes to order, consult Asona)

S4-25 (Tasmanian Oak)



Diamond Mesh (Tasmanian Oak)

S7-75 (American Oak)



Frangapani (American Oak)

RS12-150 (Tasmanian Oak)




P25-40 D (Kopenhagen)

P12-30-40 (Walnut)







P19-19 (Maple)

P15-60 (Maple)



P50-100 (American Oak)



\* Colour representations are as close as printing permits. Always make your colour selections from an actual sample, not from a digital screen.

A range of standard and custom perforations and woodgrains\* are available. Consult Asona for shop drawings.

ISO 9001:2015 Registered Firm No. NZ1014

© 2024 Copyright ASONA Ltd Asona, Triton 25 Woodlook, Sonaris are trade marks of Asona Ltd, Donn DX is a trade mark of Rondo Building Services Pty Ltd

\*All dimensions are nominal. We reserve the right to change specifications.

Ref. Triton 25W-24.10

Asona Ltd. Office & Factory  
6 Mahunga Drive, Māngere  
Bridge, Auckland 2022  
New Zealand  
NZBN: 9429036035175

New Zealand  
T: +64(0)9 525 6575  
E: info@asona.co.nz  
W: www.asona.co.nz

Australia  
T: 1 800 240361  
E: info@asona.com.au  
W: www.asona.com.au

**asona**

**Standard Sizes** (Special sizes to order, consult Asona)

Item #	Description	600 x 600mm	600 x 1200mm	1200 x 1200mm
P15-60	15mm hole @ 60mm centres, square pattern	●	●	
P25-40 D	25mm hole @ 40mm centres, diagonal pattern		●	
P50-100	50mm hole @ 100mm centres, square pattern	●	●	
P12-30-40	12, 30, 40mm holes, random pattern	●	●	
P19-19	19 x 19mm square holes	●		
S4-25	4mm slot @ 25mm centres	●	●	
S7-75	7mm slot @ 75mm centres	●	●	●
S10-100	10mm slot @ 100mm centres	●	●	●
RS12-150	12mm x 150mm random slot	●	●	●
D4070	Diamond Mesh	●	●	
H4040	Hexagonal Mesh	●	●	
FP200	Frangipani	●	●	
SQ5075	50 x 50mm square holes @ 75mm centres	●		
SQ75100	75 x 75mm square holes @ 100mm centres	●		
Non-perf	No perforations	●	●	●

**Technical Specifications:****Environmental Impact:**

Contains >80% recycled local glass waste, low VOC <0.002 Mg/M<sup>2</sup>/hr per ASTM D5116, damaged or soiled panels can be resur-faced to extend useful life and reduce construction waste/ landfill.

**Laminate Finishes:**

Triton 25 Woodlook™ is available in a range of perforated design wood print LPL finishes. Non-perforated is also available.

**Maintenance:**

Clean with a vacuum, soft brush or damp cloth.  
Re-surfacing of damaged panels available, consult Asona.

**NZ Building Act**

This product is not subject to a warning or ban under Section 26.

**NZ Building Code Compliance:**

- B2 Durability – Clause B2.3.1 (c) (i): Asona ceiling tiles with only normal maintenance will have a minimum durability of at least 5 years when installed in accordance with; manufacturer's installation requirements and AS/NZS 2785:2020.
- C3 Fire – Clause C/AS2 3.4(a): Asona Triton 25W has a Fire Material Group Number 1-S by NZBC verification method C/VM2 Appendix A, tested in accordance with ISO 5660 or ISO 9705. (NCC BCA C1.10 clause 4, spec A2.4 clause 4. Group 1)

**Packaging Take Back Scheme: (NZ only)**

Flat pack cartons on site and return to Asona for reuse. (NZ only)  
Renew & Reuse Stewardship Program:  
Soiled or damaged panels can be resurfaced with new Sonatex or Sonaris laminates for reuse in the ceiling. Helps extend life cycle and reduce construction waste. Register on practical completion.

**Thermal Resistance:**

R 0.7 m<sup>2</sup>C/W

**Tolerances:**

Width and length +/- 2 mm

**Warranty:**

15 year limited warranty against manufacturing defects.

**Weight:**

1.5 kg/m<sup>2</sup>

**Installation:**

Shall not commence until the building is watertight and dry. This product is designed to be mounted into a two-way exposed grid system and installed to manufacturer's and AS/NZS 2785:2020 Standard's requirements. Seismic design may require a suitably qualified engineer. Hold down clips may be required in areas of wind uplift, and/or air grilles used to balance air pressure. Care shall be taken when handling tiles to avoid damage.

**Specification:**

Ceiling system shall be Asona Triton 25 Woodlook™ high sound absorbing ceiling as manufactured by Asona Ltd Auckland NZ Tel: +64(0)9 525 6575 info@asona.co.nz. Selected panel shall be size 25 x ( ) x ( )mm, square edge with decorative low pressure laminate finish wood-look print) (American Oak)(Tasmanian Oak) (Maple)(Kopenhagen)(Walnut) Sonaris perforation type ( ), sound absorption NRC ( ), Fire Group 1-S. Suspension system shall be Rondo Donn DX two way exposed grid system with 19 x 22 mm wall angle, grid colour (white) (black). Contractor shall flat pack packaging and return to Asona for reuse and register the ceiling with Asona Renew and Reuse product stewardship program on practical completion.  
(Asona ceiling Masterspec 5311AS specification available).



ISO 9001:2015 Registered Firm No. NZ1014

© 2024 Copyright ASONA Ltd Asona, Triton 25 Woodlook, Sonaris are trade marks of Asona Ltd, Donn DX is a trade mark of Rondo Building Services Pty Ltd  
\*All dimensions are nominal. We reserve the right to change specifications.  
Ref. Triton 25W-24.10

Asona Ltd. Office & Factory  
6 Mahunga Drive, Māngere  
Bridge, Auckland 2022  
New Zealand  
NZBN: 9429036035175

New Zealand  
T: +64(0)9 525 6575  
E: info@asona.co.nz  
W: www.asona.co.nz

Australia  
T: 1 800 240361  
E: info@asona.com.au  
W: www.asona.com.au

**asona**